

FIRST RE-ESTABLISHMENT

GCDB 500140

Quarter corner common to Sections 34 and 35, Township 40 South, Range 3 West, W.M.
 $V = 19\frac{1}{4}^\circ$

Found at the corner, the 12 x 12 x 5-inch stone marked " $\frac{1}{4}$ " set in 1882 by S. W. Lackland, now tipped over.

I drove in exact location from which above stone came, a 1 x 36-inch Galvanized iron pipe 34 inches into ground with 2½-inch bronze disc marked:

Jackson County 1980
T40S R3W
34 | 35
¼S

From which I found original bearing trees marked by above surveyor:

- Ponderosa Pine stump, 24-inch diameter with " $\frac{1}{4}$ S BT" scribes visible in burnt faces bears Record: N89°E, 5.28 feet to face.
- Fir stob, 40-inch diameter with healed double blazes bears S35°W, 7.10 feet to center of tree at lower blaze. Record: S35°W, 4.62 feet.

I marked new trees "CS" "BT" and took measurements to center of tree at lower blaze:

- Douglas Fir, 12-inch diameter bears S37°E, 40.4 feet.
- Ponderosa Pine, 12-inch diameter bears S6°W, 33.4 feet.

Corner is 35.0 feet North of ridge; course East-West.

April 29, 1980
B. Malotte
Witness: T. Newcomb, USFS

Approved by: Edward McGinty
County Surveyor