

FIRST RE-ESTABLISHMENT

GCDB 500700

Section corner common to Section 34 and 35, Township 39 South, Range 3 West, and Section 2 and 3, Township 40 South, Range 3 West, W.M. $V = 17\frac{1}{2}^\circ$

Found, projecting 12 inches the 2-inch diameter iron pipe with GLO brass cap marked:

T39S	R3W
S34	S35
S 3	S 2
T40S	
1917	

As recorded by Wright & Mensch in 1917.

Original BTs recorded by S. Truax in 1857, found as follows:

- White Oak, 17-inch diameter, with scribe marks visible in partly exposed face bears $S18^\circ E$, 28.76 feet to center. Record, $S18^\circ E$, 28.38 feet.
- White Oak, 14-inch diameter, containing reverse impression of scribe marks bears $N65^\circ W$, 35.45 feet to center. Record $N65^\circ W$, 36.30 feet.
- Original N.E. and S.W. BTs now gone.

BTs marked by Wright and Mensch in 1917 found as follows:

- The stump, 16-inch diameter, of a down fir, scribed "40S W BT SC" in exposed face bears $S33^\circ W$, 64.19 feet to center. Record $S35^\circ W$, 64.68 feet.
- The stump, 30-inch diameter, of a down fir, scribed "39S R3W S34 BT SC" bears $N36^\circ W$, 105.6 feet to center. Record, $N35^\circ W$, 105.6 feet.
- N.E. BT (1917) is now gone.

Note: In 1882 S. Lackland, reports corner to be a marked stone, 17x12x9-inch. A 15x14x7-inch stone marked with a cross on one end was found disturbed about 10 feet West Southwest (downhill) of corner.

I mounded stones around corner, deposited found marked stone alongside, mark the following trees C.S. BT and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 15-inch diameter bears $N10\frac{1}{2}^\circ E$, 35.50 feet
- White Oak, 7-inch diameter bears $S60\frac{1}{2}^\circ E$, 34.04 feet.
- White Oak, 4-inch diameter bears $S31^\circ W$, 38.40 feet.
- Douglas Fir, 18-inch diameter bears $N58^\circ W$, 58.39 feet.
- Brushed and blazed line runs East from corner.

December 5, 1977
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor