

FIRST RE-ESTABLISHMENT

GCDB 540200

Quarter corner common to Sections 26 and 35, Township 40 South, Range 3 West, W.M. $V=19^\circ$

Found at the corner, 17 x 10 x 5-inch stone firmly in place with "¼" marked on North face as set by S. W. Lackland in 1882.

In exact location from which it came, I drove a 1 x 36-inch Galvanized iron pipe 30 inches into ground with 2½-inch diameter bronze disc marked:

Jackson County 1980
T40S R3W
26
¼S —
35

From which I found original bearing trees marked by above surveyor:

- Dead and down Pine, about 24-inch diameter with "BT" scribe visible in burnt face bears Record: $N47^\circ E$, 25.74 feet to estimated face.
- Laurel, 17-inch diameter with healed blazes bears Record: $S80^\circ W$, 16.92 feet to estimated face.

I marked new trees "CS" "BT" and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 11-inch diameter bears $S10\frac{1}{2}^\circ W$, 3.8 feet.
- Douglas Fir, 8-inch diameter bears $N65\frac{3}{4}^\circ W$, 11.15 feet.

Location marker placed about 300 feet East of corner on 60-inch diameter Fir on East side of Slick Ear Trail and Creek; course Southerly.

Corner lies on top of ridge course: Southeasterly.

May 8, 1980
B. Malotte
J. Gallegos

Approved by: Edward McGinty
County Surveyor