

## FIRST RE-ESTABLISHMENT

GCDB 600400

Section corner common to Sections 13, 14, 23 and 24, Township 40 South, Range 3 West, W.M.  
 $V = 20\frac{1}{2}^\circ$

Found firmly set, 17 x 6 x 4-inch stone, marked with chiseled "X" on top.

I replaced said stone with a 1 x 36-inch Galvanized iron pipe, set 32 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1977	
T40S R3W	
14	13
<hr/>	
23	24

- The single remaining original bearing tree, recorded by S. W. Lackland in 1882, now a rotted Fir stump, containing scribed "T403WS" in opened face bears Record:  $S42^\circ E$ , 10.56 feet to scribed face.
- Laurel sprouts found at record location of original NE BT.

I deposited found stone alongside corner, mark the following trees CS BT and took measurements to center of trees at lower blaze:

- Douglas Fir, 19-inch diameter bears  $N85\frac{1}{4}^\circ E$ , 37.67 feet.
- Douglas Fir, 15-inch diameter bears  $S19\frac{1}{2}^\circ E$ , 36.64 feet.
- Laurel, 20-inch diameter bears  $S56^\circ W$ , 22.64 feet.
- Douglas Fir, 9-inch diameter bears  $N55^\circ W$ , 21.58 feet.

Corner position is about 300 feet East of location marker on 18-inch diameter pine located on top of (main) N-S ridge about 1,350 feet North of landing at end of road.

Corner is also located on small N-S ridge, 40 feet East of draw C.  $N20^\circ E$ . Same draw bears North about 100 feet.

February 9, 1977  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor