

FIRST RE-ESTABLISHMENT

GCDB 600600

Section corner common to Section 1, 2, 11 and 12, Township 40 South, Range 3 West, W.M.
 $V = 17^\circ$

Found, firmly set, a 12 x 12 x 8-inch quartz stone, (Record, 16 x 15 x 12-inch) marked with cross on top.

I replaced stone with a 1 x 36-inch Galvanized iron pipe set 27 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1975	
T40S R3W	
2	1

11	12

The only remaining original BT, recorded by S. Lackland in 1882, now a Yellow Pine snag, 6 feet high, 24-inch diameter, containing scribe marks in burned face bears Record: S40°W, 55.44 feet to scribed face.

I deposited original stone alongside corner, marked new trees CS BT and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 8-inch diameter bears N78°E, 12.92 feet.
- Douglas Fir, 15-inch diameter bears S33°E, 16.25 feet.
- Black Oak, 14-inch diameter bears S4½°W, 23.06 feet.
- Ponderosa Pine, 10-inch diameter bears N78°W, 11.67 feet.

Corner lies (½ mile North of ¼ corner, alongside road) on small North-South ridge, 2 chains South of top of hill.

December 9, 1975
R. Frost
T. Newcomb, USFS

Approved by: Edward McGinty
County Surveyor