

## RST RE-ESTABLISHMENT

GCDB 600640

Quarter corner common to Section 1 and 2, Township 40 South, Range 3 West, W.M.  $V = 19\frac{1}{2}^\circ$

From the following evidence at the location described below, I set a 1 x 36-inch Galvanized iron pipe, 25 inches in the ground, with a 2½-inch bronze disc marked:

Jackson County 1977  
T40S R3W  
¼S  
2 | 1

Original bearing trees recorded by S. Lackland in 1882, found as follows:

- A rotted and burned Ponderosa Pine snag, about 16-inch diameter 8 feet high, scribed "¼"S" and "BT" in opened faces bears Record: N6°E, 23.76 feet to scribed lower face.
- White Oak, 15-inch diameter, with healed blazes bears Record: S13°W, 25.74 feet to the estimated face.
- **Note:** A 27-inch diameter Douglas Fir stands between corner and original SW BT.

A mark the following trees CS BT and take measurement to center of trees at lower blaze:

- Douglas Fir, 12-inch diameter bears S40½°E, 21.93 feet.
- Douglas Fir, 10-inch diameter bears N76°W, 14.35 feet.

Corner lies 25 feet East of small draw, C. N-S and about 180 feet South of location marker on 24-inch diameter White oak, located at the head of above-noted draw and at the South end of large (dozer cleared) clearing.

January 13, 1977  
B. Malotte  
R. Frost

Approved by: Edward McGinty  
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

## SECOND RE-ESTABLISHMENT

GCDB 600640

Quarter corner common to Sections 1 and 2, Township 40 South, Range 3 West, W.M.

Found at the corner position, exposed 8 ins., the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1<sup>st</sup> Re-establishment in 1977, marked:

JACKSON COUNTY 1977  
T40S R3W  
¼S  
2 | 1

Original bearing trees recorded by S. Lackland of the GLO in 1882, found and measured to center at base:

- Sawed rotted Pine stump brs. record; N6°E, 23.8 ft.
- Hollow Oak snag with partially healed blazes, brs. record; S13°W, 25.7 ft.

Bearing trees recorded on said 1<sup>st</sup> Re-establishment, found with healed double blazes and measured to center at lower blaze:

- D. Fir snag, brs. record; S40½°E, 21.9 ft.
- D. Fir, now 16 ins. diam., brs. record; N76°W, 14.4 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- W. Oak 7 ins. diam. brs. N23°E, 25.6 ft.
- B. Oak 6 ins. diam. brs. S54¼°E, 9.6 ft.
- D. Fir 6 ins. diam. brs. S5¼°W, 24.4 ft.

Corner lies approx. 1700 ft. east of dirt road at a saddle near end of said road.

December 19, 2011

H. Durkee

Kerry Bradshaw  
Jackson County Surveyor

P. – 101

V. – 16°