

FIRST RE-ESTABLISHMENT

GCDB 640400

Quarter corner common to Sections 13 and 24, Township 40 South, Range 3 West, W.M. $V=17^\circ$

Found, the 12 x 7 x 6-inch stone (record 14 x 12 x 12-inch) marked as recorded by S. W. Lackland in 1882. Said stone found, broken and dislodged from its original position.

At a location determined from the following original BTs, I set a 1 x 36-inch Galvanized iron pipe 28 inches in the ground with a 2½-inch bronze disc marked:

T40S R3W
¼S 13
—
24
C.S.
1975

Original BTs found as follows:

- A Ponderosa Pine, 23-inch diameter, with healed blazes bears Record: $N86^\circ E$, 23.76 feet.
- A Douglas Fir snag, 17-inch diameter, 20 feet high, containing "S" and "BT" in exposed faces bears $S55^\circ W$, 17.16 feet. (Record: $S78^\circ W$, 17.16 feet.)

I deposited original stone alongside corner as a memorial, marked the following trees CS BT and took measurements to center of trees at lower blaze:

- A Douglas Fir, 8-inch diameter bears $N53^\circ E$, 34.85 feet.
- A Douglas Fir, 17-inch diameter bears $S41^\circ W$, 35.37 feet.
- A double Madrone, found marked "FSRM" bears $N37^\circ W$, 6.81 feet to center of tree at base.

March 18, 1975
K. Weaver
G. Cunningham
T. Newcomb, USFS
J. Darling, USFS

Approved by: Edward McGinty
County Surveyor