

FIRST RE-ESTABLISHMENT

GCDB 640500

Quarter corner common to Section 12 and 13, Township 40 South, Range 3 West, W.M. $V = 20^\circ$

From the following evidence at the location described below, I set a 1 x 36-inch Galvanized iron pipe 30 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1977
T40S R3W
12
¼S —
13

Original bearing trees recorded by S. Lackland in 1882 found as follows:

- The stump hole of a down Ponderosa Pine snag, about 40-inch diameter containing scribe marks visible in burned faces bears Record: $N55^\circ W$, 29.70 feet.
- The stump hole of a down Fir, 38-inch diameter, scribed "¼S" in opened face bears $S66^\circ W$, 32.00 feet. Record: $S74^\circ W$, 23.76 feet.

Witness trees recorded by J. Crump on USFS corner report (no date), on file, found as follows:

- Ponderosa Pine, 7-inch diameter with scribe marks visible in partly healed single face bears $S29^\circ E$, 1.32 feet to center of tree. Record: $S29^\circ W$, 1.32 feet.
- Ponderosa Pine, 7-inch diameter with healed single blaze bears $N20^\circ W$, 2.64 feet to center of tree. Record: $N20^\circ E$, 2.64 feet.
- Above trees apparently scribed in 1966 per found J. Crump location marker.

I marked new trees CS BT and took measurements to center of trees at lower blaze:

Ponderosa Pine, 7-inch diameter bears $S32\frac{1}{2}^\circ W$, 20.60 feet.

Douglas Fir, 10-inch diameter bears $N60\frac{1}{2}^\circ W$, 13.30 feet.

Corner lies on blazed (original) E-W line at top of E-W ridge.

January 25, 1977

B. Malotte

R. Frost

Approved by: Edward McGinty

County Surveyor