

FIRST RE-ESTABLISHMENT

GCDB 640600

Quarter corner common to Sections 1 and 12, Township 40 South, Range 3 West, W.M. $V = 20^\circ$

Found the single remaining bearing tree recorded by S. Lackland in 1882, now a down and rotted White Oak, about 18-inch diameter, containing reverse impression of scribed "1/" and "BT".

From the preceding evidence, I set a 1 x 36-inch Galvanized iron pipe 24 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1977
T40S R3W
1
¼S —
12

From which:

- The base and stump hole of the above-described original bearing tree (located on top of ridge) bears Record: $S50^\circ W$, 60.06 feet.
- The original 12 x 10 x 5 inches stone, Record: 15 x 12 x 7 inches marked: "¼" is found (broken) about 10 feet East (downhill) from corner.

I deposited original stone, alongside corner, mark the following trees CS BT and took measurements to center of trees at lower blaze:

- Ponderosa Pine, 13-inch diameter bears $S58^\circ W$, 32.00 feet.
- Ponderosa Pine, 9-inch diameter bears $N18^\circ W$, 5.15 feet.

Corner lies about 300 feet South of draw C. Easterly-Westerly and 60 feet NE of the corner of small opening.

January 18, 1977
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

SECOND RE-ESTABLISHMENT

GCDB 640600

Quarter corner common to Sections 1 and 12, Township 40 South, Range 3 West, W.M.

Found at the corner position, exposed 6 ins. with the original stone alongside, the 1 in. diam. galv. iron pipe with a 2½ ins. diam. brass cap set on 1st Re-establishment in 1977, marked:

JACKSON COUNTY 1977
T40S R3W
1
1/4S —
12

Single remaining original bearing tree recorded by S. Lackland of the GLO in 1882, rotted oak remains, br. record; S50°W, 60.1 ft. to center of debris.

Bearing trees recorded on said 1st Re-establishment, found with healed double blazes and measured to center at lower blaze:

- Pine, dead and down, brs. record; S58°W, 32.0 ft.
- Pine snag 10 ins. diam. brs. record; N18°W, 5.2 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- P. Pine 6 ins. diam. brs. S30¼°E, 12.3 ft.
- P. Pine 10 ins. diam. brs. N78½°E, 6.1 ft.
- W. Oak 6 ins. diam. brs. S54¼°W, 26.3 ft.

Corner lies approx. 450 ft. northwesterly from the end of an old spur road.

November 21, 2011

H. Durkee

Kerry Bradshaw
Jackson County Surveyor

P. – 80

V. – 16°50'