

FIRST RE-ESTABLISHMENT

CORNER COMMON TO SECTIONS 1 AND 36 ONLY

GCDB 700100

Northeast corner of Section 1, Township 41 South, Range 3 West, as establishment by Samuel W. Lackland under contract No. 429 dated January 5, 1882.

Found the original quartz corner stone and all four original bearing trees. For corner, set a 1"x36" galvanized iron pipe, 33" in the ground on the North edge of said stone.

From which:

- The original bearing tree (now a 45" Yellow Pine with scribe marks visible) bears North 45° West, 18.7 feet;
- The original bearing tree (now a 20" Fir) bears South 27° East, 47.8 feet;
- The original Northeast bearing tree is now obscured from the corner;
- The original bearing tree (now a 32" Laurel with scribe marks visible) bears South 55° West, 57.9 feet.

From said pipe corner, I establish the following new witness trees:

- A 10" Fir, scribed "CS-BT" bears South 76° West, 24.3 feet;
- An 8" Fir, scribed "CS-BT" bears South 33° West, 23.8 feet;
- A 10" Fir, scribed "CS-BT" bears North 9° East, 13.0 feet.

October 1960
F. A. Roberts
O. Blankenship
Florence Hall, Present

Approved by:
Mark E. Boyden
Deputy County Surveyor

SEE NEXT PAGE FOR SECOND RE-ESTABLISHMENT

**SECOND RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 1 AND 36 ONLY
GCDB 700100**

Northeast corner of Township 41 South, Range 3 West, W.M. as established by Samuel W. Lackland under contract No. 429, dated January 5, 1882.

At the corner, found projecting 4 inches, the 1x36-inch Galvanized iron pipe set on First Re-establishment, in 1960, with (disturbed) 20x12x8-inch quartz stone (No discernible marks.) alongside.

Replaced said pipe with and deposited it alongside, a 2-inch diameter by 31-inch long galvanized iron pipe set 25 inches in ground with a 2½-inch diameter brass cap marked:

```

T40S T41S
R3W | R2W
 36 |
-----| 6
      | 1
C.S. 1981
T41S

```

From which original bearing trees recorded by S. W. Lackland in 1882, found and measurements taken to center of trees:

- Douglas Fir snag, 27-inch diameter with healed blazes bears N65°E, 131.93 feet. Record: N56°E, 130.68 feet.
- Douglas Fir, 18-inch diameter with (re)healed blazes bears S28°E, 48.14 feet. Record: 46.20 feet.
- Laurel, 30-inch diameter, now hollow bears S55°W, 58.49 feet. Record: S55°W, 58.08 feet.
- Yellow Pine stob, 22-inch diameter with face alongside containing scribe marks including "T40S R3W S3, BT" bears N48°W, 20.23 feet. Record: N45°W, 18.48 feet.

Bearing trees marked on First Re-establishment, found and measurements taken to center of trees at lower blaze:

- Douglas Fir, 15-inch diameter with healed blazes bears N8°E, 13.50 feet. Record: N9°E, 13.0 feet.
- Douglas Fir, 9-inch diameter, now dead, with healed blazes bears S32°W, 24.08 feet. Record: S33°W, 23.8 feet.
- Douglas Fir, 11-inch diameter with healed blazes bears S74½°W, 24.70 feet. Record: S76°W, 24.3 feet.

Marked new trees "CS" "BT":

- Douglas Fir, 10-inch diameter bears S53½°E, 22.03 feet to center of tree at lower blaze.

Corner lies about S45°E, 85 feet from switch back in dirt road.

October 8, 1981

R. Frost

R. Templin

Witness: T. Newcomb, USFS

Edward McGinty

County Surveyor

V = 17°

P. -164