

FIRST RE-ESTABLISHMENT

GCDB 700640

Quarter corner common to Section 6, Township 40 South, Range 2 West, and Section 1, Township 40 South, Range 3 West, W.M. $V = 23^\circ$

Found firmly set, the original 14 x 12 x 6-inch stone, Record: 14 x 10 x 10-inch marked "¼" on West face, by S. Lackland in 1882.

I replaced said stone, with a 1 x 36-inch Galvanized iron pipe, set 20 inches in the ground with a 2½-inch bronze disc marked:

Jackson County 1977
T40S
¼S
1 | 6
R3W R2W

Original bearing trees recorded by Lackland found as follows:

- Pine stump core, about 10-inch diameter, (with section alongside containing partial scribed "¼S" and "BT" in burned faces) bears $S32^\circ W$, 28.38 feet to estimated face position. Record: $S45^\circ W$, 32.34 feet to estimated face.
- White Oak, 9-inch diameter, with healed blazes bears $N45^\circ W$, 32.34 feet to estimated face. Record: $N22^\circ W$, 28.38 feet.

I mounded stones around corner, deposited original stone alongside, mark the following trees CS BT, and took measurements to center of trees at lower blaze:

- Black Oak, 5-inch diameter bears $N48^\circ E$, 13.83 feet.
- Douglas Fir, 10-inch diameter bears $N60^\circ W$, 5.65 feet.

Corner lies on South slope 6.6 feet North of draw C. $S80^\circ W$.

January 19, 1977
B. Malotte
R. Frost

Approved by: Edward McGinty
County Surveyor