

FIRST RE-ESTABLISHMENT


MS154_SquawLakePlacerClaim_Cor5

GCDB 131300

SQUAW LAKE PLACER MINING CLAIM, Claim #37, Corner #5. Mineral Survey #154, dated 1887 by J. S. Howard located on Section line between Sections 19 & 30, Township 40 South, Range 3 West, W.M.


Fd., the single original Bearing Tree, recorded by J. S. Howard in 1887, now a rotted, Black Oak stump, approximately 22 ins. (56 cm) diam., containing reverse impression of scribed "BT".

From the preceding original evidence I set a 1 x 36 ins. (2.5 x 91 cm) G.I. pipe, 35 ins. (89 cm) in the ground with a 2½ ins. (6 cm) bronze disc mkd.:



I mark the following trees "CS" "BT" and take measurements to center of trees at lower blaze:

- Ponderosa Pine, 10 ins. (25 cm) diam., brs. N25°10'E, 7.07 ft. (2.15 m).
- Douglas Fir, 13 ins. (33 cm) diam. brs., S74°W, 22.43 ft. (6.84 m)
- A fd. 2½ ins. (6 cm) diam. iron pipe, projecting 7 ins. (18 cm) with BLM brass cap mkd:



As recorded on 1977 BLM dependent re-survey, brs. S58°06½'E, 16.60 ft. (506 m).

BASIS OF BEARING: E. McGinty (ORLS 301), survey in progress.

Corner lies about 110 ft. (33 m) West of foot of hill.

October 4, 1979

J. Gallegos
B. Malotte
R. Frost

Approved by: Ed. McGinty
County Surveyor