FIRST RE-ESTABLISHMENT

MS154_SquawLakePlacerClaim_Cor8 GCDB 830040

SQUAW LAKE PLACER MINING CLAIM, Claim #37, Corner #8. Mineral Survey #154, dated 1887 by J.S. Howard located in the NW Quarter of Section 30, Township 40 South, Range 3 West, W.M.

In a found ring of stone, I set a 1 x 36 ins. $(2.5 \times 91 \text{ cm})$ G.I. pipe 29 ins. (74 cm) in the ground with a $2\frac{1}{2}$ ins. (6.4 cm) bronze disc mkd:



From which,

• The root hole and base of the single original bearing tree, now a rotted pine snag, about 15 ins. (38 cm) diam., scribed "BT" brs record; \$15°W, 17.16 ft. (5.23 m).

I mk new trees CS BT and take measurements to center of trees at lower blaze:

- Douglas fir, 9 ins. (23 cm) diam., brs \$33°E, 30.32 ft. (9.24 m).
- Douglas fir, 10 ins. (25 cm) diam., brs \$60°W, 11.06 ft. (3.37 m).

Corner lies about 525 ft. (160 m) East of County road.

December 8, 1975 R. Frost

T. Newcomb, USFS

J. Darling, USFS