


**FIRST RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 31 AND 6 ONLY
GCDB 100700**

The closing corner to Township 40 and 41 South, Range 2 West, W.M.

At the closing corner, found firmly set, the original 14 x 11 x 12-inch basalt stone marked with 6 grooves on the South and East face, with a mound of stone to the Southeast as recorded by E. B. Henry in 1909.

Replaced said stone with, and deposited it alongside, a 2-inch diameter by 31 inches long, galvanized iron pipe set 24 inches in the ground with 2½-inch diameter brass cap marked:



From which bearing trees reported on Survey No. 4767, dated 1971, found and measurements taken to center of trees:

- Yellow Pine, 9-inch diameter, scribed "683" in partially healed blaze bears N51½°E, 19.95 feet. Record: N52°E, 20.2 feet.
- Douglas Fir, 8-inch diameter with scribe marks visible in partially healed blaze bears S47½°E, 18.85 feet. Record: S45¾°E, 19.4 feet.
- Douglas Fir, 8-inch diameter with scribe marks visible in partially healed blaze bears N62°W, 11.95 feet. Record: N63½°W, 11.7 feet.

Note:

- No bearing trees were recorded by E. Henry in 1909.
- The ¾-inch diameter iron pipe noted on Survey No. 4767 was found lying (disturbed) alongside corner.

Corner lies on North, South and East blaze lines.

October 8, 1981
R. Frost
R. Templin
Witness: T. Newcomb USFS

Edward McGinty
County Surveyor

V = 20°

P. -165