

**FIRST RE-ESTABLISHMENT
CORNER COMMON TO SECTIONS 5 AND 6 ONLY
GCDB 200700**

Closing corner to Sections 5 and 6, Township 41 South, Range 2 West on the north line of said township.

At the (closing) corner, found firmly set, the original 12x10x6-inch stone, marked "CC" on the South side, by E. B. Henry in 1908.

Replaced with and deposited found stone alongside, a 2x31-inch Galvanized iron pipe, set 25 inches in the ground in a mound of stone, with 2½-inch diameter brass cap marked:

1981
C.S.
—
S6 | S5
T41S
R2W
C.C.

Original bearing trees found:

- Cedar, 17-inch diameter, with healed single blaze bears S45°E, 35.59 feet to center of tree. Record: 36.96 feet.
- Cedar, 12-inch diameter, scribed "41S R2W S6 BT" in exposed single face bears Record: S68°W, 21.12 feet to center of tree.
- The brass cap (BLM) corner of Sections 31 and 32, T40S, R2W bears West, 34.00 feet.

Corner lies at Southwest corner of clear-cut logging unit.

October 30, 1981

R. Frost

R. Templin

Witness: T. Newcomb - USFS

Edward McGinty

County Surveyor

V = 18°

P. -175