

FIRST RE-ESTABLISHMENT

GCDB 400700

Section corner common to Sections 33 and 34, Township 40 South, Range 2 West, and Sections 3 and 4, Township 41 South, Range 2 West, W.M.

Found projecting 12 inches, the 2-inch diameter iron pipe, recorded as set by Marshall Wright in 1916 with a standard GLO 2½-inch diameter brass cap marked:

T40SR2W	
S33	S34

S4	S3
T41S	
1916	

Note: Wright reported that he set an iron post alongside a decayed post. In 1908, Eugene B. Henry reported that the post had disappeared and at the corner point set a basalt stone 15 x 12 x 8-inch from found bearing trees. I found a stone 2 feet SW from 1916 monument with 3 grooves East and West.

Original bearing trees recorded by McKenzie and Eckelson in 1879 and re-recorded by Wright in 1916, found and measured to the center of tree at base:

- Broken off Fir stump 35-inch diameter with remains alongside bears N6°E, 23.90 feet. Record (1916) 23.76 feet.
- White Fir snag 45-inch diameter scribed "R2WS4BT" on opened single blaze bears Record: (1916) S50°W, 4.62 feet.
- These bearing trees re-recorded by Wright have been re-scribed. I opened alongside the found 1916 face of the SW bearing tree and found double blazed and scribed faces dating back to 1879.

Original bearing tree recorded in 1916 found

- White Fir snag 38-inch diameter scribed "S33BT" visible on single partially healed blaze; bears Record: N71°W, 81.18 feet.

Marked new trees "CS" "BT" and took measurements to the center of tree at lower blaze:

- White Fir 5-inch diameter bears S10½°E, 5.70 feet.
- White Fir 7-inch diameter bears N32°E, 27.45 feet.
- Douglas Fir 23-inch diameter bears S85°W, 28.90 feet.

Corner is located on steep North slope.

December 26, 2000

T. Newcomb

Roger Roberts
County Surveyor

V = 17½°

P. -85