

FIRST RE-ESTABLISHMENT

GCDB 500640

Quarter corner common to Sections 2 and 3, Township 41 South, Range 2 West, W.M.

Found near the corner position, laying on the ground and possibly never set, the 1 x 36 ins. flanged galv. iron pipe with a 2½ ins. diam. brass cap, recorded as set by the GLO in 1916, marked:

¼
S3 | S2
1916

From the following original evidence, reset said monument at corner position and raised a mound of stones. Monument is now protruding 18 ins.

Original bearing trees recorded by M. Wright of the GLO in 1916, found and measured to center at base:

- D. fir, now 31 ins. diam. with a healed blaze, brs. record; S82½°E, 17.2 ft.
- Fir snag with a partially healed burnt face revealing scribe marks "¼ S3 BT", brs. record; West, 18.5 ft.

Mark new bearing trees "CS" "BT" and take measurements to center of trees at lower blaze:

- W. Fir 5 ins. diam. brs. N6½°W, 16.0 ft.
- S. Fir 6 ins. diam. brs. S43½°E, 7.8 ft.

Corner lies approx. 750 ft. west of gravel spur road that goes to a cabin at Kettle Belly Glade.

July 30, 2012

H. Durkee

Scott Fein
Deputy Jackson County Surveyor

P. – 16
V. – 14°05'